



EVC04

Establishing a NEW STANDARD in the commercial refrigeration industry.

Innovative high efficiency counter top cooler, designated to keep and display Coca Cola products. Perfect for self checkout areas.



KEY FEATURES



ELECTRONIC TEMPERATURE CONTROLLER

Our controller assures an optimal performance of the cooler, making the product temperature ideal for its consumption.



ELECTRONIC FAN MOTORS

Electronic fan motors allow a better performance, using only a fraction of the energy required by a shaded pole motor.



HIGH EFFICIENCY GLASS DOORS

"Low-e" double panel argon gas filled glass-pack with an extruded insulated plastic frame, making this door the most energy efficient in its category.



LED PERIMETER LIGHTING


LED lighting system, uses a portion of the energy of regular fluorescent lights, and need no replacement for seven years.




CYCLOPENTANE INSULATION

CFC and HFC free Cyclopentane foam is eco-friendly and a high efficiency insulator.


EVC04



TOP VIEW



FRONT VIEW



SIDE VIEW

TECHNICAL SPECIFICATIONS

External Dimensions	H:	32 3/4"	830 mm
	W:	21 1/4"	540 mm
	D:	22 5/8"	576 mm
Internal Dimensions	H:	28 5/8"	726 mm
	W:	18"	458 mm
	D:	18 3/4"	476 mm
Weight	Gross:	96.3 lb	43.7 kg
	Crated:	98.1 lb	44.5 kg
Volume		3.9 ft ³	111.0 lts
Capacity	53':		160
Doors		1	
Shelves		2	
20 oz bottle capacity	Total:		60
	Facings:		6

REFRIGERATION DATA

Energy Consumption (kWh/24h)	1.454
Refrigerant R134a (kg)	0.280
Compressor (hp)	1/10
Evaporator	Dynamic
Temp range	32°F to 44.6°F

ELECTRICAL DATA

Amps (A)	2.0
Volts (V)	115
Frequency (Hz)	60
Lighting	LEDs
Cord Length	118" 3000 mm
Plug type	NEMA 5-15P



IMBERA USA L.L.C.

245 TownPark Drive Suite 145
Kennesaw, GA 30144

www.imberacooling.com

* Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (Low maintenance high performance).
Dimensions rounded up to the nearest inch or millimeter.
Specifications subject to change without notice.