

# VRD37<sub>SD</sub>

Establishing a NEW STANDARD in the commercial refrigeration industry.



Compact Counter top with stainless Steel top, LED, Energy Star rated, ideal for self checkout areas.

## ELECTRONIC TEMPERATURE CONTROLLER

Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.

## LED PERIMETER LIGHTING

LED lighting system, uses a portion of the energy of regular fluorescent lights, and need no replacement for seven years.

## SLIDING DOORS

An alternative for reduced space establishments, its sliding effect keeps doors inside of the cooler cabinet. The internal springs make the doors go back up to the initial position by themselves

## HIGH EFFICIENCY GLASS DOOR

Equipped with double panel glass and low-e film to reduce condensation. Door hinge is equipped with a self-closing system to ensure the door closes safely, and returns to original position, without any damages.

## PLASTIC FRONT GRILL

Its differentiated and modern design provides superior impact resistance and is easy to remove for condenser maintenance.

## ELECTRONIC FAN MOTORS

Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer useful life fan motor.




## CYCLOPENTANE INSULATION

Eco-friendly, recyclable and high efficiency cabinet insulation.



## TECHNICAL SPECIFICATIONS

<b>External Dimensions</b>	H:	78 5/8"	1997 mm
	W:	47 3/8"	1203 mm
	D:	30 3/8"	770 mm
<b>Internal Dimensions</b>	H:	60 1/2"	1537 mm
	W:	43 1/8"	1095 mm
	D:	25 3/4"	652 mm
<b>Dimensions w/packaging</b>	H:	82 1/2"	2097 mm
	W:	49 1/2"	1258 mm
	D:	32"	813 mm
<b>Shelf Size</b>	W:	20 1/2"	520 mm
	D:	20 5/8"	524 mm
<b>Weight</b>		434.3 lb	197.0 kg
<b>Weight w/packaging</b>		453.0 lb	205.5 kg
<b>Shelves</b>		10	
<b>Capacity 20 oz</b>	Flat	490	
	Gravity	420	



## REFRIGERATION DATA

<b>Energy Consumption (kWh/24h)</b>	5.300 kWh/day
<b>Voltage</b>	115/60
<b>Horse power</b>	1/2
<b>AMPS</b>	10.0

## LOGISTIC

<b>Trailer Loads</b>	40':	24
	53':	31
<b>Certifications</b>	UL:	✓
	ES:	✓
	UL/EPH:	✓

\* Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (Low maintenance high performance).  
Dimensions rounded up to the nearest inch or millimeter.  
Specifications subject to change without notice.

IMBERA USA L.L.C.

245 TownPark Drive Suite 145

Kennesaw, GA 30144

[www.imberacooling.com](http://www.imberacooling.com)