

# G319

Establishing a NEW STANDARD in the commercial refrigeration industry.



Large single door cooler, LED, Energy Star rated, our most popular unit.

## LED LIGHTING SYSTEM

Our new brighter 220+ Luxes LED lighting uses a fraction of the energy of regular fluorescent lights.

## PLASTIC FRONT GRILL

Its differentiated and modern design provides superior impact resistance and is easy to remove for condenser maintenance.

## HIGH EFFICIENCY GLASS DOOR

Equipped with double panel glass and low-e film to reduce condensation. Door hinge is equipped with a self-closing system to ensure the door closes safely, and returns to original position, without any damages.

## LOW MAINTENANCE CONDENSER

Imbera's finless condenser designed to minimize maintenance. Drastically reduces Total Cost of Ownership. Prevents dust that blocks air flow, to save energy and extend the life of the compressor.

## ELECTRONIC FAN MOTORS

Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer useful life fan motor.

## ELECTRONIC TEMPERATURE CONTROLLER

Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.



## CYCLOPENTANE INSULATION

Eco-friendly, recyclable and high efficiency cabinet insulation.



## TECHNICAL SPECIFICATIONS

<b>Exterior Dimensions</b>	H:	78 3/4"	2000 mm
	W:	29 1/2"	750 mm
	D:	27 1/2"	700 mm
<b>Interior Dimensions</b>	H:	60 1/2"	1536 mm
	W:	25 1/2"	649 mm
	D:	21 3/8"	542 mm
<b>Dimensions w/packaging</b>	H:	82 5/8"	2100 mm
	W:	32 1/4"	820 mm
	D:	29 7/8"	760 mm
<b>Shelf Size</b>	W:	24 3/4"	630 mm
	D:	19 5/8"	497 mm
<b>Weight</b>		114.6 lb	52.0 kg
<b>Weight w/packaging</b>		123.5 lb	56.0 kg
<b>Shelves</b>		5	
<b>Capacity 20 oz</b>	Flat	240	



## REFRIGERATION DATA

<b>Energy Consumption (kWh/24h)</b>	3.040 kWh/day
<b>Voltage</b>	115/60
<b>Horse power</b>	1/4+
<b>AMPS</b>	5.2

## LOGISTIC

<b>Trailer Loads</b>	40':	42
	53':	60
<b>Certifications</b>	UL:	✓
	ES:	✓
	UL/EPH:	✓

\* Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (Low maintenance high performance).  
Dimensions rounded up to the nearest inch or millimeter.  
Specifications subject to change without notice.

IMBERA USA L.L.C.

245 TownPark Drive Suite 145

Kennesaw, GA 30144

[www.imberacooling.com](http://www.imberacooling.com)