

VRA-03 EXPRESS

This open-air countertop cooler has transparent sides allowing a greater product visibility and increasing impulse purchases.



KEY FEATURES



ELECTRONIC TEMPERATURE CONTROLLER:
Our standard controller maintains temperature efficiently based on surrounding conditions, self adjusting to the right temperature for your products.



LED PERIMETER LIGHTING:
LED lighting system, uses a portion of the energy of regular fluorescent lights, and need no replacement for seven years.



CYCLOPENTANE INSULATION:
CFC and HFC free Cyclopentane foam is eco-friendly and a high efficiency insulator.



PLASTIC HEADER:
Our highly durable and resistant plastic parts do not rust and can be fully recycled at the end of the cooler's life cycle.

TECHNICAL SPECIFICATIONS

External dimensions	H: 32 5/8"	830 mm
	W: 15 5/8"	398 mm
	D: 26 1/2"	673 mm
Internal dimensions	H: 24 1/8"	613 mm
	W: 12 1/2"	318 mm
	D: 12 5/8"	320 mm
Weight	Gross: 96.2 lb	43.6 kg
	Crated: 98.14 lb	55.5 kg
Capacity ¹	2.20 ft ³	62.38 lts
Trailer load	53': 240	
Doors	N/A	
Shelves	2	
20 oz bottle capacity	Flat shelves: 32	
	Gravity feed: N/A	
12 oz can capacity	Front facing: 4	
	Total: 48	


REFRIGERATION DATA

Energy consumption	9.28 Kwh/24h*
Refrigerant	R-134a
Compressor	1/5 hp
Evaporator	Forced air
Temp. range	32 °F to 44.6 °F


ELECTRICAL DATA

Amps	5.8 A*	
Voltage	115 V	
Lighting	LEDs	
Cord length	120"	3048 mm
	Plug type	
		NEMA 5-15P

TOP VIEW



FRONT VIEW



SIDE VIEW



¹Based on ANSI/AHAM HRF-1

*Based on ANSI/AHAM T2-2005

Metric dimensions rounded up to the nearest inch and millimeter.

Specifications subject to change without notice.

WARRANTY

One year limited warranty on all parts and labor, an additional 4 year warranty on compressor. (USA and Canada only)